

1205 TRAILER

Pure Water Trailer System

The small compact BrenderUp 1205 trailer system is an excellent trailer system for on-site and on road. With 13" wheels for ease of towing, lockable ABS lid, gas struts, jockey wheel and tailgate as standard, this is a high-quality trailer specification. As the trailer is unbraked, and 750kg gross payload, there is no BE+1 license required in the UK.



Trailer Features

- Single axle, BrenderUp Aluminium sides for durability, longevity, strength & security
- All steel work galvanised or plated
- Phenolic 12mm resin coated ply floor with Line-x waterproof system.
- Protected rear light clusters
- Lockable ABS lid complete with gas struts
- 50mm pressed steel ball coupling (c/w secondary coupling)
- V-shaped drawbar
- Jockey Wheel
- 175R13C Radial wheels & tyres



Trailer Features

- Smartank® 400Ltr capacity tank system, full onboard RODI filtration with booster pump to provide efficient filtration output.
- Dual Operators via 2 x 80m Hiviz Streamline® Hose on mounted heavy duty hose reels and 2 x 12v 100psi pumps
- Filtration Full 5-stage purification system including
- pre-filtration (sediment, carbon, granular activated carbon),
- RO Membrane, and De-Ionising polishing resin.
- High capacity 12v gel battery, offers a full working day operation.
- Integrated intelligent Numax battery charger, with external charging point, allowing charging onsite if required.
- External ports for ease of filling and charging whilst trailer remains locked.
- Solenoid valve for auto shut-off to prevent tanks from over filling.





Using the Smartank® flat tank 400Ltr system, the baffled tank ensures the low centre of gravity maximises the stability during transportation. With the equipment cabinet mounted at the front of the tank, at the door opening, operation has never been easier...

The 1205 Trailer's Pumps, controllers and filters enclosed for protection but easily accessible, via the opening of the Smartank® cabinet, maintenance and filter changes are simply and quickly achieved.

Operators can adjust the flow rates of the pumps by V16 digital flow controllers, or by a wireless remote controller (Optional). This allows the operator to choose the flow rates to suit the cleaning job, saving and conserving water when less intense water flow is needed.

This Trailer is suitable for vehicles with towing capacity of at least 750kg. High capacity baffled tank integrated into lightweight chassis for easy towing. DOT road specification, single axle, integrated lights, and indicators. Supplied with European standard coupling and jockey wheel. Conforms to UK & EU regulations.

1205 TRAILER

Country Of Origin	England
Number Of Operators	1-2
Payload	650kg
Unladen Weight	205kg
Gross Vehicle Weight	750kg
Tank Size	400kg
Maximum Height	1300mm
Maximum Length	3000mm
Maximum Width	1600mm

