BRAVO" 650

RODI / DI / Delivery Tank Systems

Streamline® water filtration systems are designed to be used for window cleaning, solar panel cleaning, boat cleaning, etc. where a spot-free finish is essential. To achieve this, the system has a series of filters to produce pure water with a reading of Oppm... However, the filters require maintenance from time to time to maintain optimum efficiency.



Bravo™ 650ltr (No Filtration) Includes:

- 650ltr Baffled Tank With Vented Tank Lid
- Full Stainless Steel Frame
- 1x Streamline® SFC16 Digital Flow Controller
- 1x Shurflo® Pump 12v 100psi / 3.8lpm C/W Inline Filter
- 1x Float Valve Shut-Off On Tank Inlet
- 2mtrs Of Wiring With Battery Terminals To
- Connect Onto A 12v Battery

*Please Note A Battery Is Not Included With This System (See SP100 For A Split Charge Relay Kit To Suit A EURO 5 Vehicle Or SP100-PRO To Suit A EURO 6 Vehicle)

••••••

Bravo™ 650ltr DI (DI Filtration) Includes:

All Features Above +

- 1x Filterplus® 6×18. 7ltr Filter Vessel Filled With DI Resin
- 1x Metal DI Filter Clamp And Mounting Board
- 1x HM Digital Handheld TDS/Temperature Meter With
- 1x Hoselock Male Outlet Connection On DI Vessel

Bravo™ 650ltr RODI (RODI Filtration) Includes:

All Features Above +

- 40" Reverse Osmosis Membrane and Stainless Steel Housing Capable of Producing Up to 120ltrs Per Hour, Thus Filling The 650ltr Tank In Roughly 4-5hrs
- Filterplus® Triple 10" Inline Prefilter Set See replacement Filter Set (KITO2310-001)











Build and pump locations may vary* Image Shows Typical BRAVO650-D-RODI Fit Out

Bravo™ 650 System Varient Specificatons						
Part No.	No. Of Operators	Filteration	Length	Width	Height	Dry Weight
BRAVO650	1	None	145cm	63cm	102cm	87kg
BRAVO650-D	1 - 2	None	145cm	90cm	102cm	95kg
BRAVO650-DI	6	DI	145cm	90cm	102cm	102kg
BRAVO650-D-DI	1 - 2	DI	145cm	90cm	102cm	110kg
BRAVO650-RODI	1	RODI	145cm	90cm	102cm	128kg
BRAVO650-D-RODI	1 - 2	RODI	145cm	90cm	102cm	136kg



