

SOFTCLEAN™ DOSE

Chemical Dosing Softwash Trolley

This product can mix Algo Clear (or similar) accurately with water at a pre-set ratio on demand. Connect to a water source to produce a chemical mix either via the pump or directly through the Dosatron dosing unit. The Softclean™ Dose has receptacles for two 5ltr chemical containers.



Features & Benefits

- Durable stainless steel frame.
- Streamline® V16 flow controller to maximise flow and save wasting solution.
- Low profile flat-free tyres, for rough terrain.
- Built-in booster pump and lithium-ion battery. (5 hour run time)
- Holds two 5ltr chemical containers.
- Lightweight frame with handle mounted on the front plate for easy lifting and handling
- Dosatron metering valve for accurate chemical dosing.

SOFTCLEAN™ DOSE	
Country Of Origin	England
Maximum Height	1230mm
Maximum Length	420mm
Maximum Width	360mm
Dry Weight	16.5kg
Inlet Pressure Requirement	20psi
Inlet Water Flow Requirement	15Lpm
Optimum Operating Pressure	85psi
Standard Water Inlet Connection	Hoselock connection
Minimum Operating Temperature	5°C
Maximum Operating Temperature	40°C
Water Flow (optimum output)	15Lpm
Water Quality Range (MINI l/h - Maxi l/h)	n/a
External Adjustable Injection Rate	0.15-8.75 %
Maximum Viscosity of concentrate	400cSt at 20c
Battery Type	12v Li-Ion
Operating Time	5hrs



Please Note - Not suitable for use with Sodium Hypochloride